



SPECIFICATION

EMERGENCY LED CEILING LIGHT

3 YEARS WARRANTY








FEATURES:

- Input Voltage: 110-240V AC, 50/60Hz
- CCT: 2800-3300K, 4000-4500K, 6000-6500K
- Power factor >0.85
- CRI>80
- Frame finish: white
- Excellent heat dissipation
- When the main power is on, it can work as normal light without affecting the emergency function.
When the main power is off, it works as emergency light.
- More than 35000hrs lifetime
- Patented Product, Counterfeiting not allowed

APPLICATION:

- Office
- Corridor
- Parking area
- Garage
- Subway
- Shopping mall,
- Hospital etc.

Model	CL34936918																		
Input	100-240V AC, 50/60Hz																		
Power Consumption	18W																		
Power Factor	>0.9																		
Light Source	0.5W SMD LED																		
Color Temperature	2800-3300K, 4000-4500K, 6000-6500K																		
CRI	>80																		
Output Lumen	1200lm																		
Luminous Efficiency	67lm/W																		
Diffuser	PMMA																		
Beam Angle	120°																		
Lux Diagram in non-emergency mode	<div><div><div>120°</div></div></div> <table><thead><tr><th>H(m)</th><th>Lux</th><th>Ø (m)</th></tr></thead><tbody><tr><td>1</td><td>299.3</td><td>3.49</td></tr><tr><td>2</td><td>74.83</td><td>6.99</td></tr><tr><td>3</td><td>33.26</td><td>10.48</td></tr><tr><td>4</td><td>18.71</td><td>13.98</td></tr><tr><td>5</td><td>11.97</td><td>17.47</td></tr></tbody></table>	H(m)	Lux	Ø (m)	1	299.3	3.49	2	74.83	6.99	3	33.26	10.48	4	18.71	13.98	5	11.97	17.47
H(m)	Lux	Ø (m)																	
1	299.3	3.49																	
2	74.83	6.99																	
3	33.26	10.48																	
4	18.71	13.98																	
5	11.97	17.47																	
Luminous Intensity Distribution Diagram in non-emergency mode	<div><div></div></div>																		
Material of Housing	Aluminum/Iron																		
Color of Housing	Silver/White																		
Dimmension	ø395x113mm																		
Product Line Chart	<div><div></div></div>																		
Connection	fast connector																		
Installation Method	Surface mounted																		
IP Rating	IP21																		
Working Temperature	-20~50℃																		
Working Lifetime	>35000HRS																		

WARNING FOR INSTALLATION:

- The product must be installed by professional technicians
- Ensure mains supply is switched off before commencing work
- Do not touch LED while installing
- Please acknowledge the light from the LED is very bright, do not look directly into the LED light
- Do not disassemble the product

MAINTENANCE

- Cut off the mains power first
- Use soft cloth to clean the surface
- The PMMA cover can be cleaned by alcohol
- Do not use thinner to clean the PMMA cover