

## LED EMERGENCY EXIT LIGHTS

Lifespan:>50000Hours

Comply To:CE/ROHS

### TECHNICAL DATA



Model No.	: EB99024930
Power Consumption	: 5W
Power Supply	: AC110V/AC220V;50HZ/60HZ
Lighting Resource	: LED
Standby Time	: >3Hours
Charing Time	: <24Hours
Battery Type	: Ni-Cd
Battery Capacity	: 3.6V/800mAH
Safety Features	: Low Volt Cut-Off Preventing : Battery Overdischarge Preventing
Material	: Iron With Epoxy Powder Coating
Body	: PVC
Diffuser	: PVC
Mounting	: Ceiling
Cable Entry	: Ø21.00mm Hole
Size:	: 340*280*90mm
Weight	: 1.50kgs
Warranty	: 3Years(Battery 1 Year)

### ORDERING GUIDE

(Please check with Sales Dept. if Customisation is Required)

Ordering No.	Diffuser
--------------	----------

EB99024930(M)



EB99024930(L/R)



EB99024930(U)



EB99024930(D)



### KEY FEATURES

- >Diffusers Changeable
- >Ceiling Mountable
- >Quick & easy to install and maintain
- >Low Power Consumption
- >Long life
- >3Years Warranty(Battery 1Year)

### PACKAGE INFORMATION

Inner Box	: 390*280*90mm
Gross Weight	: 2.00Kgs
Carton Size	: 410*580*500
Qty./Carton	: 10pcs
20FCL	: 2500Pcs
Loading Qty. 40FCL	: 5200Pcs
40HQ	: 7000Pcs

Specifications Subject To Changes Without Prior Notice

1

**SUNWIND LIGHTING COMPANY LTD.**

7th Floor,Block H,Juyin Industrial Park,Ganli Road 1#,Buji,Shenzhen,China 518112

T: 0086 755 8661 0835

F: 0086 755 8661 0201

E: [sales@sunwindled.com](mailto:sales@sunwindled.com)

W: [www.sunwindled.com](http://www.sunwindled.com)



**SUNWIND**